

# Pengutex

## Technical Data Sheet



### Product description

Penguin Pengutex is an acrylic copolymer based exterior wall cover which is durable to bad weather conditions and can be given ornaments with roller. It has a wide spreading function and can be used one layer. It helps walls to breath with the help of special filling components.

### Sphere of usage

It can be used on the surfaces like exterior wall, priming, plaster, concrete, plasterboard and betopan. The temperature of surface must be between +5°C and +30°C during application and humidity can be maximum 80%. Penguin Universal Primer must be applied to surface before Penguin Pengutex application. It's ready for usage, but can be thinned with maximum 10% water.

### Film thickness and spreading rate

	Minimum	Maximum
Film thickness, dry ( $\mu\text{m}$ )	60	100
Film thickness, wet ( $\mu\text{m}$ )	75	130
Theoretical spreading rate ( $\text{m}^2/\text{l}$ )	1	1.5

### Physical specifications

Color	Can be painted with water-based pastes
Dry residue content (weight %)	77 $\pm$ 2
Density ( $\text{gr}/\text{cm}^3$ )	1.85 $\pm$ 2
Viscosity	150 $\pm$ 5
Shine	Matt

### Surface preparation

Surface must be cleaned from dust, dirt, oil substances and old paints.

### Application methods

Spray	Airless spray or convention spray can be used
Brush	Appreciate
Roller	Appreciate

### Drying duration

Drying duration depends on weather conditions, thickness and number of layers. In the table below, approximate drying duration is shown in different temperatures.

- Surface must be good-ventilated (Open air or free air circulation)
- Paint must be applied in recommended thickness
- Thickness must be determined according to the number of layers

<b>Weather temperature</b>	<b>10°C</b>	<b>23°C</b>
<b>Top drying</b>	9-10 hour	3 hour
<b>Full drying</b>	30 hour	4 hour

### **Storage conditions**

Paint must be stored without opening in dry, cool, good ventilated places where there is not any risk for high temperature and sparks. It is recommended to mix the paint before usage.

### **Packing types**

Paint is produced in 1.5 kg, 4 kg, 10 kg və 25 kg plastic containers.

### **Health and safety rules**

Follow the rules on the containers. Store in depots where there is not any risk for high temperature and sparks. Use in good-ventilated places. If there is a contact with paint, first clean it with proper solvent and then wash skin with water and soap. If eyes contact with paint, it must be cleaned water and doctor intervention is important.