

# PVA Parquet

## Technical Data Sheet



### Product description

Penguin PVA Parquet is a polyvinyl acetate based glue. It shows perfect adhesive function on wood, paper and dry priming.

### Sphere of usage

It can be used to stick any kind of wood, paper. Moreover, it can be used for increasing adhesive function of dry priming. The temperature of surface must be between +5°C and +30°C during application and humidity can be maximum 80%.

### Physical specifications

<b>Color</b>	Transparent
<b>Dry residue content (weight %)</b>	21±2
<b>Density (gr/cm<sup>3</sup>)</b>	1.02±2

### Drying duration

Glue dries in 30 minute - 2 hour interval depend on the thickness of glue.

### Storage conditions

Paint must be stored without opening in dry, cool, good ventilated places where there is not any risk for high temperature and temperature under -5°C. It is recommended to mix the paint before usage.

### Packing types

Paint is produced in 0.75 kg, 2.5 kg, 8 kg and 28 kg plastic containers.

### Qablaşdırılma şəkli

0.75 kq, 2.5 kq, 8 kq, 18 kq və 28 kq-lıq plastmas qablarda istehsal olunur.

### Health and safety rules

Follow the rules on the containers. Store in depots where there is not any risk for high temperature and sparks. Use in good-ventilated places. If there is a contact with paint, first clean it with proper solvent and then wash skin with water and soap. If eyes contact with paint, it must be cleaned water and doctor intervention is important.