

Travertino

Technical Data Sheet



Product description

Penguin Travertino is a mineral-based and natural decorative coating material that provides a travertine aspect on the surface of interior walls.

- It is a decorative paint that can create different effects depending on the application method of the user.
- Due to the high water vapor permeability, make it easier for the water vapor to be expelled and the damage to be breathed.
- Because it is water-based, it does not harm human health and the environment.

Sphere of usage

On all interior walls, plaster coating, gross concrete and wooden surfaces; it is used together with its appropriate primer after the surface preparation.

Surface preparation

Before application, the surface must be cleaned of old paint residues, dust, dirt and oil residues. In order to obtain a smooth surface, the surface should be coated with Penguin Soft Coat, and then, if necessary, the surface should be sandblasted. The surface should be primed with Penguin Decoprimer.

Surface temperature should be between +5-+30°C, relative humidity should not exceed 80%.

Application Instructions

- After opening Penguin Travertino should be mixed until homogeneous
- Need to apply with a stainless steel trowel without dilution the first layer and the thickness must be at least of 1mm.
- Wait minimum 6 hours before applying the second layer
- Before the thorough-drying, you can give the effect on the surface with a special sponge
- In order to obtain a proper finish, the surface should be polished with a steel trowel
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

Drying duration

The drying time mainly depends on the weather conditions, the thickness of the applied layer and the number of applied layers. The table below shows the approximate drying time of the paint depending on the air temperature.

- The area to be painted should be well ventilated (Open air or free air circulation)
- The paint should be applied at the recommended thickness
- The Relative humidity should not exceed 70%

Weather temperature	10°C	23°C
Top drying	6 hours	3 hours
Full drying	96 hours	48 hours
Second layers, min	12 hours	6 hours

“CMT GROUP” LLC

Address: Badamdar shos. 27, Baku, Azerbaijan

Tel: (+994 12) 345 04 05

Faks: (+994 12) 345 04 06

E-mail: office@cmt.com.az

Web-site: www.penguin.az



Travertino

Technical Data Sheet



The information shown above has been determined by following the rules. The drying time may increase or decrease depending on the film thickness, ventilation, the paint system on the surface, and the operations the paint undergoes.

Theoretical consumption

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

-1 lt covers 1.75 – 2,35 m² of surface

-1 kg covers 1,00 – 1,35 m² of surface

-The paint consumption for 1 m² area is 425 – 570 ml and 750 – 1000 gr

Storage conditions

The paint should be stored in dry, cool, well-ventilated warehouses without direct sunlight, between +5°C and +35°C without opening the lid. It should be mixed well before use. Shelf life is 3 years in unopened packaging.

Packing types

Paint is produced in 10kg and 25kg plastic containers.

The implementing operator

This product is intended for professional use. The applicator or operator must be experienced and knowledgeable about the product. The person in question shall mix and apply the paint according to the specification. Employees participating in the application must be provided with safety equipment.

Product color

It can be painted in any color with water-based pastes. There may be slight variations in product color from batch to batch.

Attention

The above information is based on results obtained from laboratory tests and field applications. In applications outside the company's control, the company is solely responsible for the quality of the paint. It is not responsible for problems that may arise from implementation and application errors.

Health and safety regulations

Follow the instructions on the container. Store in warehouses where there is no possibility of high temperatures and sparks. Use in well-ventilated areas. In case of contact with the skin during use, it should be washed with a suitable solvent and then with soap and water. In case of eye contact, wash with plenty of water and seek medical attention if necessary.

H317 May cause an allergic skin reaction.

“CMT GROUP” LLC

Address: Badamdar shos. 27, Baku, Azerbaijan

Tel: (+994 12) 345 04 05

Faks: (+994 12) 345 04 06

E-mail: office@cmt.com.az

Web-site: www.penguin.az



Travertino

Technical Data Sheet



P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 If on skin: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Note: "CMT GROUP" LLC reserves the right to change the information on the technical data page without notice.

"CMT GROUP" LLC

Address: Badamdar shos. 27, Baku, Azerbaijan

Tel: (+994 12) 345 04 05

Faks: (+994 12) 345 04 06

E-mail: office@cmt.com.az

Web-site: www.penguin.az

