

Soft Coat

Technical Data Sheet



Product description

Penguin Soft Coat is a ready to use and high-quality water based universal putty. Can be used up to 6mm without any cracking.

Sphere of usage

Penguin Soft Coat can be used on the surfaces like interior walls, ceilings, plasters, cardboard surfaces and ext. Suitable for application with a steel trowel.

Surface preparation

Surface must be cleaned from dust, dirt, oil substances and old paints. The temperature of surface must be between +5°C and +30°C during application and humidity can be maximum 80%.

Drying duration

Drying duration depends on weather conditions, thickness and number of layers up to 24 hours. When the air temperature is below 15°C and the relative humidity is above 65%, the drying time can be longer.

Paint consumption

1l/m² for 1mm thickness depending on the surface smoothness and application method. Expendable surface to be painted affects roughness and porosity, as well as the method and conditions of painting.

Storage conditions

Paint must be stored without opening in dry, cool, good ventilated places where there is not any risk for high temperature and sparks. It is recommended to mix the paint before usage.

Packing types

Penguin Soft Coat is produced in 25KG plastic containers.

The implementing operator

This product is intended for professional use. The applicator or operator must be experienced and knowledgeable about the product. The person in question shall mix and apply the paint according to the specification. Employees participating in the application must be provided with safety equipment.

Product color

It can be painted in any color with water-based pastes. There may be slight variations in product color from batch to batch.

Attention

The above information is based on results obtained from laboratory tests and field applications. In applications outside the company's control, the company is solely responsible for the quality of the paint. It is not responsible for problems that may arise from implementation and application errors.

"CMT GROUP" LLC

Address: Badamdar hwy. 27, Baku, Azerbaijan

Tel: (+994 12) 345 04 05

Fax: (+994 12) 345 04 06

E-mail: office@cmt.com.az

Web-site: www.penguin.az



Soft Coat

Technical Data Sheet



Health and safety rules

Follow the rules on the containers. Store in depots where there is not any risk for high temperature and sparks. Use in good-ventilated places. If there is a contact with paint, first clean it with proper solvent and then wash skin with water and soap. If eyes contact with paint, it must be cleaned water and doctor intervention is important.

S 2	: Keep out of reach of children.
S 3 / 7	: Keep the container in a cool place with the mouth closed/
S 24 / 25	: Avoid contact with eyes and skin.
S 29	: Do not dispose of in drains.
S 46	: In case of ingestion, consult a doctor immediately, show the container or label.

Note: "CMT GROUP" LLC reserves the right to change the information on the technical data page without notice.

"CMT GROUP" LLC

Address: Badamdar hwy. 27, Baku, Azerbaijan

Tel: (+994 12) 345 04 05

Fax: (+994 12) 345 04 06

E-mail: office@cmt.com.az

Web-site: www.penguin.az

